



# MAGIC BUTTON

## Anti-Vandal Slim Backlit PIN Standalone Controller



**This advanced 500 user anti-vandal standalone controller features shiny blue illuminated metal keys for PIN code user credentials. The keypad has a slim Rugged metal construction ideal for installations in high traffic environments. This model is epoxy filled, designed to withstand the rigors of the outdoor environment, and has advanced programming options.**

### GENERAL DESCRIPTION

The AC-Q41SB anti-vandal controller has a unique combination of large backlit metal keys and a built-in heater. It offers a higher level of user accessibility in low light areas.

AC-Q41SB has an attractive slim profile, free from sharp edges, ideal for installations where style and functionality are highly important.

This feature-rich unit offers all weather operation, with flexible programming capabilities including a unique "code search" for simple user management.

Non-volatile memory protects the storage of user database, modes and parameters.

### MAIN FEATURES

- 500 users can have PIN user credentials for granting access
- Smooth attractive design, with anti-vandal construction
- Highly-visible blue backlit keypad
- 3 operational Security Levels can be selected with special PIN codes
- Supports up to 8-digit PIN codes, with timed wrong code lockout after 3 wrong attempts
- 2 tri-colored LEDs and integral sounder for programming and operation
- Wide range of low voltage AC/DC power input

### PROFESSIONAL GRADE FEATURES

- Optical tamper detection
- Automatic internal heater prevents key freeze at -20°C (4°F).
- 10 programmable modes for auxiliary input and output (2 Amp Form C Relay)
- 2 Amp Form C Lock Strike Relay, for fail-safe and fail-secure, with input for REX
- Supports: Door Ajar, Forced, Shunt, Monitor, and Secure mode

### ELECTRICAL SPECIFICATIONS

- 12-24 VDC from regulated power supply
- 12-24 VAC from a transformer
- Relay outputs: 2A, N.O & N.C
- Inputs: N.O Dry contact

### PHYSICAL SPECIFICATIONS

- Dimensions: 120 x 76 x 22 mm
- Weight: 521g

**LIFTMASTER ELECTRONICS PTY LTD** A.B.N. 58 000 266 035  
PO BOX 54 ALEXANDRIA NSW 1435 AUSTRALIA PH: 61 2 9699 9654 FX: 61 2 9699 8443  
[www.liftmaster.com.au](http://www.liftmaster.com.au) [salesdesk@liftmaster.com.au](mailto:salesdesk@liftmaster.com.au)

As Liftmaster Electronics policy is one of constant improvement, we reserve the right to alter any part of these specifications without notice and without incurring any obligation.